

APPARATUS LOGBOOK CHART

APPARATUS	CUBIC INCHES H.P.	CYLINDERS	OPERATING RPM'S	MIN. OIL PRESSURE @ IDLE	OPERATING OIL PRESSURE	OPERATING WATER TEMP.	AUXILIARY GENERATOR	MINIMUM BRAKING PSI	AIR TANK
'75 Segrave Detroit	568 / 350 @ 2300	8 Detroit	1600 – 2300	"some"	32 – 70	160 - 185	No	80 PSI Warn @ 60	5
'75 Seagrave Cummins	855/350 @ 2100	6 Cummins	1400 – 2100	Never op Less than 30	50 - 75	160 – 185	No	80 PSI Warn @ 60	5
'77 Seagrave	855 / 250 2 2100	6 Cummins	1400 – 2100	Never op Less than 30	32 – 70	160 – 185	No	Not Given	4
'82 Seagrave	736 / 445 @ 2100	8 Detroit	1900	10	25 @ 1200 30 @ 2100	160 – 185	No	90 PSI Warn @ 60	5
'83 Seagrave	736 / 445 @ 2100	8 Detroit	1900	10	25 @ 1200 30 @ 2100	Not Given	No	90 warn @ 60	4
'85 Seagrave	736 / 445 @ 2100	8 Detroit	1900	10	25 @ 1200 30 @ 2100	170 – 195	No	90 Warn @ 70	4
'86 Seagrave	736 / 445 @ 2100	8 Detroit	1900	10	25 @ 1200 30 @ 2100	170 – 195	ONAN 600 Watts	90 PSI Warn @ 70	6
'88 Seagrave	736 / 445 @ 2100	8 Detroit	1900	10	25 @ 1200 30 @ 1200	170 – 195	ONAN 6000 Watts		4
'90 Seagrave	736 / 445 @ 1200	8 Detriot	1900	10	25 @ 1200 30 @ 2100	170 – 195	ONAN 6000 Watts	90 PSI Warn @ 70	4
'93 LTI	855 / 445 @ 1600	6 Cummins	1550 – 2100	10	35 – 45	160 – 190	ONAN 6000 Watts	90 PSI Warn @ 60	6
'95 Peterbuilt Heavy Rescue 56	855 / 460 @ 1600	6 Cummins	1700 – 2200	10	35 – 40	160 – 190	No	90 PSI Warn @ 60	6
'96 LTI	855 / 460 @ 1600 774 / 470 @ 2100	6 Cummins 6 Detroit	1550 - 2100 1550 – 2200	10 0	40 - 50 @ 2100 35 – 45	160 - 190 160 – 190	ONAN 6000 Watts	90 PSI Warn @ 60 90 PSI Warn @ 70	6
'99 LTI American LaFrance	774 / 470 @ 2100	6 Detroit	1200 – 1800	12	50@ rated	160 - 210	ONAN 6000 Watts	90 PSI Warn @ 65	6
'93 Squad	855 400 @ 2100	6 Cummins	1200	20 – 25	35 – 40	145 – 160	ONAN	90 PSI Warn @ 70	
'00 LTI American LaFrance	774 / 470 @ 2100	6 Detroit	1200 – 1800	12	50@ rated	160 - 210	ONAN 7.5 KW	90 PSI Warn @ 65	6
'01 LTI American LaFrance	774 / 470 @ 2100	6 Detroit	1200 – 1800	12	50@ rated	160 - 210	ONAN 7.5 KW	90 PSI Warn @ 65	6
'02 LTI American LaFrance	774 / 470 @ 2100	6 Detroit	1200 – 1800	12	50@ rated	160 - 210	ONAN 7.5 KW	90 PSI Warn @ 65	6